



. . . c o n n e c t i n g y o u r b u s i n e s s

LANCOM 1781A-3G (CC)

High-performance VPN router with ADSL2+ and 3G modem for highly secure site connectivity

- Certified IT security "Made in Germany" – CC EAL 4+ compliant
- Ideal for highly secure site connectivity and the protection of critical sub-areas
- Integrated multimode ADSL2+ modem, cellular modem (HSPA +, HSxPA, UMTS/3G, EDGE, GPRS)
- Encrypted data transfer over the Internet with five simultaneous IPsec VPN tunnels (optional: 25 VPN tunnels)
- Network virtualization with up to 16 networks on one device (ARF)
- Powerful firewall with intrusion detection/Denial-of-Service protection
- Additionally available: LANCOM CC Start-up Kit for a certified installation



LANCOM
Systems

The professional VPN router LANCOM 1781A-3G (CC) is ideal for public authorities, institutions, and commercial organizations that need a high level of security in their data communications: The LANCOM 1781A-3G (CC) is intended for high-security operations based on CC EAL 4+. The certification by the German Federal Office for Information Security (BSI) guarantees that the evaluation of the LANCOM products meets worldwide highest standards. The evaluation level CC EAL 4+ is the highest level of certification a commercial network product can achieve. On top of that, the LANCOM 1781A-3G (CC) comes with a field-proven scope of functionalities and interfaces. Comprehensive VPN functions enable remote sites to access the company network securely. Thanks to its integrated ADSL2+ modem, 3G modem, and powerful firewall, the LANCOM 1781A-3G (CC) offers secure connections to the Internet over a standard DSL connection – without any additional hardware. The option to operate four Internet connections at a single device makes the LANCOM 1781A-3G (CC) the ideal platform for high traffic.

More data security.

Certified IT security: Made in Germany. The LANCOM 1781A-3G (CC) is ideal for public authorities, institutions, and commercial organizations that require the security level "CC EAL 4+" (Common Criteria for Information Technology Security Evaluation, Evaluation Assurance Level 4+) as specified by the German Federal Office for Information Security (BSI). This internationally recognized seal of approval guarantees the security and confidentiality of the LANCOM 1781A-3G (CC), which an independent body has methodically examined and tested to level 4. Hence, the LANCOM 1781A-3G (CC) provides certified protection against cyber attacks to cross-site networks with pronounced security requirements and to critical infrastructures.

More performance.

The LANCOM 1781A-3G (CC) provides a balanced and modern hardware platform for a reliable operation of enterprise networks around the clock. As a professional business router, the device meets with high standards in the areas of network virtualization, security, and VPN networking. At the same time, its computing power, storage capacity, and the high-speed interfaces ensure excellent network performance even at times of heavy data traffic.

More virtualization.

The LANCOM 1781A-3G (CC) helps to make effective and economical use of IT resources. The device can simultaneously support multiple, independent networks. This is made possible by the powerful technology Advanced Routing and Forwarding (ARF). The ARF function on the LANCOM 1781A-3G (CC) provides up to sixteen virtual networks, each with its own routing and firewall settings.

The LANCOM security pledge.

LANCOM Systems GmbH is a German enterprise, with German management board, which is not subject to legal regulations or the influence of other states, requiring the implementation of backdoors or allow the sniffing of unencrypted data. The LANCOM portfolio for high-security site connectivity provides networks of enterprises and public authorities a comprehensive, guaranteed backdoor-free, and BSI-certified protection (CC EAL 4+) against cyber attacks.

UMTS modem	
Supported standards	UMTS, HSPA+ (HSPA+ with up to 21 Mbps, HSUPA with up to 5.76 Mbps), Edge, and GPRS support
UMTS and HSxPA bands	850/900/1900/2100 MHz
EDGE/GPRS bands	850/900/1800/1900 Mhz (EDGE up to max. 236kbps)
Firewall	
Packet filter	Check based on the header information of an IP packet (IP or MAC source/destination addresses; source/destination ports, DiffServ attribute); remote-site dependant and direction dependant
Extended port forwarding	Network Address Translation (NAT) based on protocol and WAN address, i.e. to make internal webservers accessible from WAN
N:N IP address mapping	N:N IP address mapping for translation of IP addresses or entire networks
Tagging	The firewall marks packets with routing tags, e.g. for policy-based routing
Actions	Forward, drop, reject, block sender address, close destination port, disconnect
Notification	SYSLOG (internally)
Security	
Intrusion Prevention	Monitoring and blocking of login attempts and port scans
IP spoofing	Source IP address check on all interfaces: only IP addresses belonging to the defined IP networks are allowed
Access control lists	Filtering of IP or MAC addresses and preset protocols for configuration access
Denial of Service protection	Protection from fragmentation errors and SYN flooding
General	Detailed settings for handling reassembly, PING, stealth mode and AUTH port
Password protection	Password-protected configuration access can be set for each interface
Alerts	Alerts via SYSLOG (internally)
Authentication mechanisms	PAP, CHAP, MS-CHAP and MS-CHAPv2 as PPP authentication mechanism
GPS anti-theft	Network protection via site verification by GPS positioning, device stops operating if its location is changes
Adjustable reset button	Adjustable reset button for 'ignore', 'boot-only' and 'reset-or-boot'
High availability / redundancy	
FirmSafe	For completely safe software upgrades thanks to two stored firmware versions, incl. test mode for firmware updates
UMTS backup	In case of failure of the main connection, a backup connection is established over the internal UMTS modem; automatic return to the main connection
VPN redundancy	Backup of VPN connections across different hierarchy levels, e.g. in case of failure of a central VPN concentrator and re-routing to multiple distributed remote sites. Any number of VPN remote sites can be defined (the tunnel limit applies only to active connections). Up to 32 alternative remote stations, each with its own routing tag, can be defined per VPN connection. Automatic selection may be sequential, or dependant on the last connection, or random (VPN load balancing)
Line monitoring	Line monitoring with LCP echo monitoring, dead-peer detection and up to 4 addresses for end-to-end monitoring with ICMP polling
VPN	
Number of VPN tunnels	Max. number of concurrent active IPSec and PPTP tunnels (MPPE): 5 (25 with VPN 25 Option). Unlimited configurable connections. Configuration of all remote sites via one configuration entry when using the RAS user template or Proadaptive VPN.
Hardware accelerator	Integrated hardware acceleration for ESP encryption and decryption (data path)
Realtime clock	Integrated, buffered realtime clock to save the date and time during power failure. Assures timely validation of certificates in any case
Random number generator	Generates high-quality randomized numbers in software
IKE	IPSec key exchange with Preshared Key or certificate (in software)
Certificates	X.509 digital self signed certificates (no CA support), compatible with OpenSSL, upload of PKCS#12 files via SCP. Secure Key Storage protects a private key (PKCS#12) from theft
RAS user template	Configuration of all VPN client connections in IKE ConfigMode via a single configuration entry
Proadaptive VPN	Automated configuration and dynamic creation of all necessary VPN and routing entries based on a default entry for site-to-site connections. Propagation of routes via RIPv2 if required
Algorithms	AES (128, 192 or 256 bit) and HMAC with SHA-1 / SHA-256 hashes
NAT-Traversal	NAT-Traversal (NAT-T) support for VPN over routes without VPN passthrough
1418-byte frame size UDP	90 Mbps

Firewall throughput (max.)	
1518-byte frame size UDP	123 Mbps
Routing functions	
Router	IP-Router
Advanced Routing and Forwarding	Separate processing of 16 contexts due to virtualization of the routers. Mapping to VLANs and complete independent management and configuration of IP networks in the device. Automatic learning of routing tags for ARF contexts from the routing table
Policy-based routing	Policy-based routing based on routing tags. Based on firewall rules, certain data types are marked for specific routing, e.g. to particular remote sites or lines
Dynamic routing	Propagating routes; separate settings for LAN and WAN. Extended RIPv2 including HopCount, Poisoned Reverse, Triggered Update for LAN (acc. to RFC 2453) and WAN (acc. to RFC 2091) as well as filter options for propagation of routes. Definition of RIP sources with wildcards
Layer 2 functions	
VLAN	VLAN ID definable per interface and routing context (4,094 IDs) IEEE 802.1Q
ARP lookup	Packets sent in response to LCOS service requests (SSH) via Ethernet can be routed directly to the requesting station (default) or to a target determined by ARP lookup
LAN protocols	
IP	ARP, Proxy ARP, IP, ICMP, PPPoE (Server), RIP-2 (Propagation), TCP, UDP
WAN protocols	
ADSL, Ethernet	PPPoE, PPPoA, IPoA, Multi-PPPoE, ML-PPP, VLAN
WAN operating mode	
xDSL	ADSL1, ADSL2 or ADSL2+ with internal ADSL2+ modem
xDSL (ext. modem)	ADSL1, ADSL2 or ADSL2+ with external ADSL2+ modem
UMTS/HSPA+	GPRS, Edge, UMTS or HSPA+ with internal UMTS modem
Interfaces	
WAN: ADSL2+	<ul style="list-style-type: none"> ■ Compliant to: ADSL2+ as per ITU G.992.5 Annex A/Annex B/Annex J/Annex M with DPBO, ADSL2 as per ITU G.992.3 Annex A/Annex B/Annex J/Annex M, ADSL as per ITU.G.992.1 Annex A/Annex B ■ Supports one virtual ATM circuit (VPI, VCI pair) at a time ■ Compliant to: Deutsche Telekom U-R2 (1TR112)
Ethernet ports	4 individual 10/100/1000 Mbps Ethernet ports; up to 3 ports can be operated as additional WAN ports with load balancing. Ethernet ports can be electrically disabled within LCOS configuration. The ports support energy saving according to IEEE 802.3az
Port configuration	Each Ethernet port can be freely configured (LAN, DMZ, WAN, monitor port, off). LAN ports can be operated as a switch or separately. Additionally, external DSL modems or termination routers can be operated as a WAN port with load balancing and policy-based routing. DMZ ports can be operated with their own IP address range without NAT
Serial interface	Serial configuration interface / COM port (8 pin Mini-DIN): 9,600 - 115,000 baud
Management	
Device Syslog	Syslog buffer in the RAM (size depending on device memory) to store events for diagnosis. Default set of rules for the event protocol in Syslog. The rules can be modified by the administrator. Display and saving of internal Syslog buffer (events) from LANCOM devices.
Remote maintenance	Remote configuration with SSH in software
SSH & Telnet client	SSH-client function (in software) compatible to Open SSH under Linux and Unix operating systems for accessing third-party components from a LANCOM router. Also usable when working with SSH to login to the LANCOM device. Support for certificate- and password-based authentication. SSH client functions are restricted to administrators with appropriate rights.
Security	Access rights (read/write) over WAN or LAN can be set up separately (SSH), access control list
Scripting	Scripting function for batch-programming of all command-line parameters and for transferring (partial) configurations, irrespective of software versions and device types, incl. test mode for parameter changes. Utilization of timed control (CRON) or connection establishment and termination to run scripts for automation.
Timed control	Scheduled control of parameters and actions with CRON service
Diagnosis	Extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, internal logging buffer for firewall events, monitor mode for Ethernet ports

Statistics	
Statistics	Extensive Ethernet and IP statistics
Accounting	Connection time, online time, transfer volumes per station. Snapshot function for regular read-out of values at the end of a billing period. Timed (CRON) command to reset all counters at once
Hardware	
Power supply	12 V DC, external power adapter (230 V) with bayonet cap to protect against accidentally unplugging
Environment	Temperature range 5–40° C; humidity 0–95%; non-condensing
Housing	Robust synthetic housing, rear connectors, ready for wall mounting, Kensington lock; 210 x 45 x 140 mm (W x H x D)
Fans	None; fanless design without rotating parts, high MTBF
Power consumption (max)	12.5 Watt
Declarations of conformity	
CC certification	LCOS Certification based on Common Criteria for Information Technology Security Evaluation (CC EAL 4+) with certificate number "BSI-DSZ-CC-0815" at the German Federal Office for Information Security
CE	EN 60950-1, EN 301 489-1, EN 301 489-24
Scope of delivery	
Manual	Hardware Quick Reference (EN, DE), Installation Guide (DE/EN/FR/ES/IT/PT/NL)
CD/DVD	Data medium with firmware, management software (LANconfig, LANmonitor, LANCAPI) and documentation
Cable	1 Ethernet cable, 3 m
Cable	ADSL cable, 3m
Antennas	Two 2 dBi dipole UMTS/GPRS antennas (850-960 Mhz and 1700-2220 Mhz)
Power supply unit	External power adapter (230 V), NEST 12 V/1.5 A DC/S, coaxial power connector 2.1/5.5 mm bayonet, temperature range from -5 to +45° C
Support	
Warranty	4 years
Options	
VPN	LANCOM VPN-25 Option (25 channels), item no. 60083
Accessories	
LANCOM CC Start-up Kit	All-in-one package for the certified start-up and highly secure configuration of LANCOM CC products based on CC EAL 4+, item no. 62910
External antenna	AirLancer Extender O-360-3G 4 dBi omnidirectional GSM/GPRS/EDGE/3G outdoor antenna, item no. 61225
External antenna	AirLancer Extender I-360-3G 2dBi GSM/GPRS/EDGE, 5dBi 3G, omnidirectional indoor antenna, item no. 60916
19" Rack Mount	19" Rackmount-Adapter, Art.-Nr. 61501
LANCOM Wall Mount	For simple, theft-proof mounting of LANCOM devices with plastic housings, item no. 61349
Item numbers	
LANCOM 1781A-3G (EU, CC)	62603
LANCOM 1781A-3G (UK, CC)	62613

LANCOM, LANCOM Systems and LCOS are registered trademarks. All other names or descriptions used may be trademarks or registered trademarks of their owners. Subject to change without notice. No liability for technical errors and/or omissions. 6/2013